

FREE STANDING COMBINATION SERIES

Model	FS Comb 3	FS Comb 5
* Flow Rate	65 GPM	100 GPM
Height	52"	
Width	36"	
Depth	34"	
Weight	575 lbs	625 lbs
Input Power	208/230/480 3 Phase 60 Cycle	
Control Power	115 Volt 1 Phase 15 Amp Max	
Primary Pump	3.0 HP	5.0 HP
Full Load Amps	8.5 / 8.0 / 4.0	13.0 / 12.2 / 6.1
Suction Inlet	2" NPT	3" NPT
Filtered Outlet	1½" NPT	2" NPT
Discharge Outlet	3" NPT	

- 3 / 5 HP Process Pump w/Strainer Basket
- Self-Cleaning Stainless Filter Element
- U/L Listed Electrical Control System
- 25u Absolute Filtered Water Quality *
- Flow Rates up to 100 GPM
- Brass Check Valves
- 35 Gallon Ballast Tank

* 25 Micron equals 0.0009 the size of a single white blood cell



* GPM Ratings may vary due to Piping Layout that may change Pump Head Curve

THIS SYSTEM IDEAL FOR:

- Applications that would make frequent bag changes difficult
- Locations that require uninterrupted flow
- Limited Underground Storage Tanking
- Low Service or Maintenance Program
- Unattended Car Wash locations
- High Volume Flow Demand

AVAILABLE OPTION:

- Stainless Steel Filter Housing