

FREE STANDING COMBINATION SERIES III

- Dual Self-Cleaning Stainless Steel Filter Element
- Lifetime Warranty on Stainless Steel Filter Element
- 25u Absolute Filtered Water Quality *
- Stainless Steel Platform, Components, & Fittings
- Stainless Steel Housing and Separator
- 3 HP / 5 HP Process Pump with Strainer Basket
- Includes UL Listed Ozone / Stainless Steel
- 24 SCFH Oxygen Concentrator
- Bio-Treatment Dosing Control
- UL Listed Electrical Control System
- ¾ HP Ozone Re-Circulation Pump
- Includes Pump Guard Advisor **
- Flow Rates up to 125 GPM
- Vortex Particle Accelerator
- Brass Check Valves

* 25 Micron equals 0.001 (the size of a single white blood cell)



Model	FS Comb Series III 3	FS Comb Series III 5
* Flow Rate	75 GPM	125 GPM
Height	62"	
Width	54"	
Depth	34"	
Weight	675 lbs	725 lbs
Input Power	208/230/480 3 Phase 60 Cycle	
Control Power	115 Volt 1 Phase 15 Amp Max	
Primary Pump	3.0 HP	5.0 HP
Full Load Amps	8.5 / 8.0 / 4.0	13.0 / 12.2 / 6.1
Secondary Pump	¾ HP @ 3.1 / 1.55 Full Load Amp	
Suction Inlet	2" NPT	3" NPT
Filtered Outlet	1½" NPT	2" NPT
Ozone Outlet	1-1/4" NPT	
Discharge Outlet	3" NPT	
Ozone Output	12 grams / Hour	
Oxygen	24 SCFH	

* GPM Ratings may vary due to Piping Layout that may change Pump Head Curve

Available Options

- Tank Level Control
- EFO (Emergency Freshwater Override)

** Limited Pump Warranty on Systems
Not Equipped with Pump Guard